

[Home](#)Signed in as Triton | [sign out](#)

RIBA Insight TT Super - Capillary Active Tanking Slurry for Concrete Structures

Support information:

- [Frequently asked questions:](#) [How does NBS Plus work?](#) | [How do I comment on my NBS Plus product data?](#) | [What is NBS Create?](#)
- [Quick links:](#) [Home](#) | [My products](#) | [How my products appear in NBS](#) | [How my products appear in NBS Create](#) | [Print this page](#)
- [Resources:](#) [NBS Newsletter, Journal and eNewsletter](#) | [Terms and Conditions, Disclaimer](#) and [Using the NBS Plus logo](#)
- [Contact details:](#) nbsplusproduction@thenbs.com | T: 0845 456 9594

The information below is the NBS Plus product entry for Triton Systems TT Super - Capillary Active Tanking Slurry for Concrete Structures.

TT Super - Capillary Active Tanking Slurry for Concrete Structures

A surface applied material which waterproofs and protects concrete. It consists of grey or white Portland cement, silica or quartz sand and a compound of active chemicals.

When applied to a concrete surface the active chemicals combine with the free lime and moisture present in the capillary track to form insoluble crystalline complexes. These crystals block the capillaries and minor shrinkage cracks in the concrete to prevent any further water ingress (even under pressure). The layer will still allow the passage of water vapour through the structure (i.e. the concrete will still be able to breathe). In addition to waterproofing the structure, Triton TT Super protects against seawater, wastewater, aggressive ground water and certain chemical solutions.

Triton TT Super is not a decorative product.

More about TT Super - Capillary Active Tanking Slurry for Concrete Structures:

[As standard](#)

TT Super - Capillary Active Tanking Slurry for Concrete Structures

- Manufacturer: Triton Systems.
- Web: www.tritonsystems.co.uk.
- Tel: +44 (0)1322 318830.
- Product reference: [\[TT Super\]](#).
[\[TT Super \(White\)\]](#).

Add product

[top ^](#)

Guidance for TT Super - Capillary Active Tanking Slurry for Concrete Structures from Triton Systems

More about TT Super - Capillary Active Tanking Slurry for Concrete Structures: [As standard](#)

As standard

TT Super:

- Withstand water pressure >12 bars @ 28 days.
- Colour: Cement grey.
- Setting time: 60 minutes.

TT Super (White):

- Withstand water pressure >7 bars @ 28 days.
- Colour: White.
- Setting time: 120-180 minutes.

Further Information


Literature:



[Triton Concrete Waterproofing Systems](#)



[Triton BS8102 \(2009\) Type A Barrier Protection.](#)

 Additional information may be available for Triton Systems from ribaproductselector.com.

Contacts:

www.tritonsystems.co.uk
technical@tritonsystems.co.uk
T: +44 (0)1322 318830
F: +44 (0)1322 524017

NBS Plus

Triton, NBS Plus Approval Site, 10 August 2012
nbsplusproduction@thenbs.com | T: 0845 456 9594