RIBA W Insight TT55 Waterproof Slurry - Cementitious Tanking Slurry for Walls and Floors

Support information:

- 🥝 Frequently asked questions: How does NBS Plus work? | How do I comment on my NBS Plus product data? | What is NBS Create?
- 🥡 Quick links: Home | My products | How my products appear in NBS | How my products appear in NBS Create | Print this page
- Resources: NBS Newsletter, Journal and enewsletter | Terms and Conditions, Disclaimer and Using the NBS Plus logo
- Contact details: nbsplusproduction@thenbs.com | T: 0845 456 9594

The information below is the NBS Plus product entry for Triton Systems TT55 Waterproof Slurry - Cementitious Tanking Slurry for Walls and Floors.

TT55 Waterproof Slurry - Cementitious Tanking Slurry for Walls and

A single component, polymer modified cement 'tanking' system for walls and floors, providing a highly effective damp proof membrane for brickwork, concrete or any cementitious substrate.

More about TT55 Waterproof Slurry - Cementitious Tanking Slurry for Walls and Floors:



Manufacturer: Triton Systems

www.tritonsystems.co.uk. - Tel: +44 (0)1322 318830. - Product Triton TT55 Waterproof Slurry.

TT33 fillet [Not required]. seals: [Required].

Add product

top ^

Guidance

for TT55 Waterproof Slurry - Cementitious Tanking Slurry for Walls and Floors from Triton Systems

More about TT55 Waterproof Slurry - Cementitious Tanking Slurry for Walls and Floors: As standard

As standard

Application:

- Walls: TT55 should be sandwiched between sand/ cement render coats. Floors: TT55 should be applied directly to the structural slab.

- Available for use when forming wall/ floor junctions.
 Fillet Seals help to ensure a smooth transition between horizontal and vertical surfaces.

Further Information

Literature:



Triton Concrete Waterproofing Systems



Triton BS8102 (2009) Type A Barrier Protection.

Additional information may be available for <u>Triton Systems from ribaproductselector.com</u>.

Contacts:

www.tritonsystems.co.uk technical@tritonsystems.co.uk T: +44 (0)1322 318830 F: +44 (0)1322 524017

NBS Plus

Triton, NBS Plus Approval Site, 10 August 2012 nbsplusproduction@thenbs.com | T: 0845 456 9594

1 of 1 10/08/2012 11:31

