




Support information:

 **Frequently asked questions:** [How does NBS Plus work?](#) | [How do I comment on my NBS Plus product data?](#) | [What is NBS Create?](#)

 **Quick links:** [Home](#) | [My products](#) | [How my products appear in NBS](#) | [How my products appear in NBS Create](#) | [Print this page](#)

 **Resources:** [NBS Newsletter](#), [Journal](#) and [eNewsletter](#) | [Terms and Conditions](#), [Disclaimer](#) and [Using the NBS Plus logo](#)

 **Contact details:** nbsplusproduction@thenbs.com | T: 0845 456 9594

The information below is the NBS Plus product entry for Triton Systems Tri-Rend - Plasticiser for Renders and Mortars.

Tri-Rend - Plasticiser for Renders and Mortars

A waterproofing, salt inhibiting and plasticizing additive for sand and cement renders and mortars.

Tri-Rend is designed to improve the workability of the mix and, after curing, provides salt resistance and water repellence. Tri-Rend is recommended for use in mortars used for internal cement rendering of walls affected by rising dampness. The product is an alkali metal soap of aliphatic fatty acids dissolved in water. The concentrate is alkaline (pH 11).

Areas of application:

One litre of Tri-Rend is diluted with water to produce 40 litres. Diluted Tri-Rend is then used as gauging water. Tri-Rend should be added to the first (10 mm) coat of cement mortar only, when applying to internal walls affected by damp. Subsequent coats do not require the addition of Tri-Rend.


Tri-Rend - Plasticiser for Renders and Mortars

- **Manufacturer:** Triton Systems.
 - **Web:** www.tritonsystems.co.uk.
 - **Tel:** +44 (0)1322 318830.
 - **Product reference:** Tri-Rend.

[Add product](#)[top ^](#)

Guidance for Tri-Rend - Plasticiser for Renders and Mortars from Triton Systems

Further Information**Literature:**

 Additional information may be available for Triton Systems from ribaproductselector.com.

Contacts:

www.tritonsystems.co.uk
technical@tritonsystems.co.uk
T: +44 (0)1322 318830
F: +44 (0)1322 524017

NBS Plus

Triton, NBS Plus Approval Site, 10 August 2012
nbsplusproduction@thenbs.com | T: 0845 456 9594